

## 1.7 LÁMINA NEGRA PERFORADA

### ESPECIFICACIONES DE PERFORADO REDONDO

NUM. DE CATÁLOGO	DIAMETRO Ø		DIST. ENTRE CENTROS		PERF. POR PULGADA	ÁREA LIBRE %
	mm	0.000"	mm	0.000"		
EO59/098	1.5	.059	2.5	.098	110	30%
EO62/125	1.6	.062	3.2	.125	72	23%
EO62/250	1.6	.062	6.4	.250	18	6%
EO78/137	2.0	.078	3.5	.137	60	30%
EO78/157	2.0	.078	4.0	.157	40	23%
EO93/157	2.4	.093	4.0	.157	47	32%
EO93/250	2.4	.093	6.4	.250	18	12%
EO98/157	2.5	.098	4.0	.157	40	36%
EO118/196	3.0	.118	5.0	.196	30	33%
E125/250	3.2	.125	6.4	.250	18	23%
E157/206	4.0	.157	5.2	.206	24	48%
E157/250	4.0	.157	6.4	.250	18	36%
E187/312	4.7	.187	7.9	.312	12	33%
E187/250	4.7	.187	6.4	.250	18	50%
E196/275	5.0	.196	7.0	.275	15	46%
E196/314	5.0	.196	8.0	.314	11	35%
E236/314	6.0	.236	8.0	.314	11	51%
E236/354	6.0	.236	9.0	.354	9	40%
E250/375	6.4	.250	9.5	.375	8	40%
E250/500	6.4	.250	12.7	.500	5	23%
E275/393	7.0	.275	10.0	.393	7	45%
E314/393	8.0	.314	10.0	.393	7	58%
E314/433	8.0	.314	11.0	.433	6	48%
E354/472	9.0	.354	12.0	.472	5	51%
E354/511	9.0	.354	13.0	.511	4	44%
E375/500	9.5	.375	12.7	.500	5	51%
E393/511	10.0	.393	13.0	.511	4	56%
E393/551	10.0	.393	14.0	.551	4	46%
E472/629	12.0	.472	16.0	.629	3	51%
E500/750	12.7	.500	19.1	.750	2	40%
E511/629	13.0	.511	16.0	.629	3	60%
E551/649	14.0	.551	16.5	.649	3	65%
E590/787	15.0	.590	20.5	.787	2	51%
E629/787	16.0	.629	20.0	.787	2	58%
E750/1000	19.1	.750	25.4	1.000	1	51%
E1000/1500	25.4	1.000	38.1	1.500	0.5	40%